



Smart 450L Sub Zero

Key benefits

Energy efficient Subzero operation

- Tropical ambient condition (41°C)
- Minimum energy consumption that can be further reduced through respective functional items
- Visible temperature display

The ideal merchandising solution for various trade channels

- Great product visibility and sufficient capacity with moderate footprint requirements
- Increased illumination to enhance impulse buying
- Indoor and outdoor placement (standard IP24)
- Self-closing door
- Low noise operation

Increased reliability and robustness

- High quality galvanized metal sheets for cabin, door frame and grid

Easy servicing

- Easy dis-/assembly and access to components e.g. front-sliding modules
- Use of quick electrical connectors

Reduced Cost of Ownership

- Low-maintenance condenser
- Standard LED illumination
- Standard Energy Management Device (EMD)

Easy to rebrand and up-brand



Activation look

Options

- Front visibility shelves (including Rotoshelf)
- Internal protector/stabilizer
- Various lock types
- Left-right door opening provision
- Door blocker
- Protection against current leakage to earth
- Enhanced aesthetics with Activation look
- LED illumination, additional on left side
- LED illuminated door logo
- Night Cover

Technical data

Dimensions	
External (W/D/H) mm	596 x 629* x 2014
Internal (W/D/H) mm	511 x 507 x 1582
Net weight (kg)	112
Footprint area (m ²)	0.37
Shelves	
Number of shelves	5
Facings per shelf	7
Shelf size (W/D) mm	495 x 425

Capacity	
500 ml (cans / glass bottles)	322 / 217
330 ml (cans / glass bottles)	497 / 320
Gross volume (Lt)	427
Transportation	
per 20' container (units)	27
per 40' container (units)	57
per 13.6m truck (units)	63

*Excluding 50mm handle & 80mm back spacer