

Smart Hybrid



Key benefits

A cooling solution for long power outages

- Tropical ambient condition (41°C)
- Eutectic capacity during power-off
- Fast pull down to benefit from the power supply availability to the maximum extent
- Enhanced insulation properties

The ideal merchandising solution for various trade channels

- Enhanced aesthetics with standard Activation look
- Strong product visibility and sufficient capacity with moderate footprint requirements
- 24hrs battery-secured illumination to maintain impulse buying also during power-off
- Indoor and outdoor placement (standard IP 24)
- Self-closing door

Increased reliability and robustness

- High quality galvanized metal sheets for cabin, door frame and grid

Easy servicing

- Easy dis-/assembly and access to components e.g. front-sliding modules
- Use of quick electrical connectors

Reduced Cost of Ownership

- Low-maintenance condenser
- Standard LED illumination

Easy to rebrand and up-brand



Options

- Internal protector / stabilizer
- Protection against current leakage to earth
- Door blocker
- LED illumination, additional on left side
- Door lock

Technical data

Dimensions	
External (W/D/H) mm	671 x 678* x 2060**
Internal (W/D/H) mm	511 x 516 x 1360
Net weight (kg)	175
Footprint area (m ²)	0.50
Shelves	
Number of shelves	4
Facings per shelf	7
Shelf size (W/D) mm	476 x 371

Capacity	
500 ml (glass bottles)	-
330 ml (cans)	266
Gross volume (Lt)	368
Transportation	
per 20' container (units)	24
per 40' container (units)	51
per 13.6m truck (units)	57

*Excluding door handle, including 20mm folded back spacer **Including rollers