

Flex 130 C Sub Zero



Key benefits

Sub-zero operation

- Product temperature between -3,5°C and + 1°C
- Visible digital temperature display

Compact size

- Small footprint combined with slim design fits every outlet and drives impulse buying

High reliability and robustness

Strong product/brand visibility

- Highly efficient LED product illumination
- Illuminated branded canopy



Options

- Aluminum door frame
- Second vertical LED lighting
- LED on door installation
- Reversible door option (not compatible with self-closing door mechanism and LED on door)
- Customized graphics and color options
- Door lock
- External door handle
- Chrome shelves
- Plastic shelf profiles

Technical data

Dimensions	
External (WxDxH) mm	403 x 439 x 1900
Internal (WxDxH) mm	325 x 343 x 1405
Net weight (kg)	72
Footprint area (m ²)	0,17
Shelves	
Number of shelves	6
Facings per shelf	8 (330 ml cans, double stacked)

Shelves (continued)	
Total facings	40 (330 ml cans, double stacked, 4 shelves)
Shelf size (WxD) mm	308 x 293
Capacity	
250 ml cans	240 (4 shelves)
330 ml cans	148 (4 shelves)
500 ml cans	96 (5 shelves)
500 ml PET	68 (4 shelves)
Gross volume (Lt)	166

Transportation	
per 20' container (units)	55
per 40' container (units)	120
per 40' HC container (units)	120
per 13.6m truck (units)	135