

Super 60 sub Zero



Key benefits

The ideal merchandising solution for all trade channels

- Self-closing door
- Indoor and outdoor placement
- Energy efficient Subzero operation in Tropical ambient condition (41°C)

High reliability and robustness

- Widely-proven ICM solution
- Aluminum door frame and metallic front grid ensure durability & robustness in harsh environmental condition
- High quality galvanized metal sheets for inner and outer cabin
- IP24

Strong cooling performance

- Top performer in hot, dusty and humid environments

Reduced cost of ownership

- Low-maintenance condenser
- LED illumination as standard

Easy servicing

- Sliding mechanism provides easy access to entire cooling system from the front without having to move the unit

Strong brand visibility

- Full size glass door for ultimate product visibility and enhanced impulse purchase
- High quality, digitally printed stickers for side panels



Options

- External protector/ stabilizer (90/110V)
- Internal protector/stabilizer
- Glass tempering/ high altitude glass
- Castor wheels
- Bottle opener & crown catcher
- Digital temperature display



Foul-free WOT



Best-in-class energy saving



Reduced noise



IPS



Enhanced LED lighting

Technical data

| Dimensions | |
|----------------------------------|--------------------------|
| External (W/D/H) mm | 739 x 630* x 2076 |
| Internal (W/D/H) mm | 655 x 540 x 1664 |
| Net weight (kg) | 128 |
| Footprint area (m ²) | 0.47 |
| Shelves | |
| Number of shelves | 5 |
| Facings per shelf | 9 |
| Total facings (cans) | 108** |
| Shelf size (W/D) mm | 623 x 444 |

| Capacity | |
|---------------------------|-------------------|
| 500 ml PET | 333** max. |
| 330 ml cans | 666** max. |
| Gross volume (Lt) | 599 |
| Transportation | |
| per 20' container (units) | 24 |
| per 40' container (units) | 51 |
| per 13.6m truck (units) | 39 |

* Excluding back spacer **with extended shelves and optional top shelf ***uncoated shelf dimms