



Key benefits

The ideal double-door ICM solution for various trade channels

- Moderate footprint and large capacity
- Indoor and outdoor placement

Customer-friendly operation

- Self-closing door

High reliability and robustness

- Widely-proven ICM solution
- Aluminum door frame and metallic front grid ensure durability and robustness in harsh environmental conditions
- High quality galvanized metal sheets for inner and outer cabin

Strong cooling performance

- Top performer in hot, dusty and humid environments

Easy servicing

- Sliding mechanism provides easy access to entire cooling system from the front without having to move the unit

Reduced cost of ownership

- Low-maintenance condenser
- Single evaporator fan
- LED illumination

Easy to rebrand and refurbish



(SD and HD versions)

Options

- Visi-shelves
- High-density shelves
- Electromagnetic lock
- Door lock
- Thermometer (digital or analogue)
- Internal protector/stabilizer
- Available in Sliding (SD) and Hinged (HD) versions

Technical data

Dimensions		Capacity	
External (W/D/H) mm	1025 x 731* x 2045	500 ml PET	490 max.
Internal (W/D/H) mm	941 x 644 x 1581	330 ml cans	980 max.
Net weight (kg)	178	Gross volume (Lt)	964
Footprint area (m ²)	0.75	Transportation	
Shelves		per 20' container (units)	15
Number of shelves	5 + 5	per 40' container (units)	33
Facings per shelf	7 + 7	per 13.6m truck (units)	36
Shelf size (W/D) mm**	458 x 543		