

# MAX 450



## Key benefits

- Modern and elegant design without canopy
- Maximum product visibility with 7 loading levels
- Optimized merchandizing effectiveness

## Technology and Performance

- Reliable and robust construction
- No maintenance condenser
- Energy Class C
- Easy serviceability with quick electrical connectors and easy access components
- Natural refrigerant R290
- Silent operation dBA <57
- Optimized airflow circulation with dual evaporator and condenser motors

## Standard Configuration

- Top sticker on door
- Side stickers
- Vertical side LED
- Easy grip handle
- Electronic thermostat
- Metallic outer cabin, inner cabin and door
- 6 adjustable shelves
- Self-closing door
- 4 rollers / 2 adjustable feet

## Options

- Light switch
- Compressor switch
- PRCD/RCCB protection
- Additional LED lighting
- Left/right door opening
- High density shelves
- Pad lock provision
- Door blocker
- Price profiles
- Electromagnetic lock & eye lock

## Technical data



Best-in-class energy saving



Low noise

Dimensions		Shelves		Capacity	
External (W/D/H) mm	<b>595 x 676* x 2012</b>	Number of shelves	<b>7</b>	500ml PET	<b>259 cert.</b>
Internal (W/D/H) mm	<b>521 x 491 x 1818</b>	Facings per shelf	<b>7</b>	330ml cans	<b>518 max.</b>
Net weight (kg)	<b>100</b>	Total facings	<b>49</b>	Gross volume (lt)	<b>472</b>
Footprint area (m <sup>2</sup> )	<b>0,38</b>	Shelf size (W/D) mm	<b>508 x 423</b>	Transportation	
		Transportation	Without PRCD	per 40' container (units)	<b>57</b>
		20' container	<b>55</b>	per 13.6m truck (units)	<b>76</b> (wide truck)
		40' container	<b>120</b>		<b>63</b> (standard truck)
		40' HC container	<b>120</b>		
		13,6m truck	<b>135</b>		

\*Including handle (32mm)